

STRUCTURAL CALCULATIONS

PROJECT:

SUGARHOUSE PARK - BIG FIELD
SUGARHOUSE PARK
SALT LAKE CITY, UT

PROJECT NUMBER:

25-039

CLIENT:

PLAYSPACE DESIGNS

DATE:


2/27/2025

BY:

SAMUEL SPANN, PE

APPROVED BY:

RYAN HAZELWOOD, PE



**HAZELWOOD
ENGINEERING**

HAZELWOOD ENGINEERING
331 S RIO GRANDE ST., STE. 160
SALT LAKE CITY, UT
P: 801-810-5061



Project #: 25-039
Project: SUGARHOUSE PARK - BIG FIELD
By: SAMUEL SPANN, PE

Date 2/27/2025

PROJECT INFORMATION

ADDRESS: SUGARHOUSE PARK
SALT LAKE CITY, UT
COUNTY: SALT LAKE
LAT: 40.72
LONG: -111.85
ELEVATION: 4413

PROJECT DESCRIPTION

FOUNDATIONS FOR PAVILION

DESIGN CRITERIA

STRUCTURE TYPE: COMMERCIAL
DESIGN CODE: 2021 IBC
RISK CATEGORY: II

DESIGN LOADS

ROOF LOADS

DL 6 PSF
LLR 20 PSF

SNOW LOADS

GROUND SNOW LOADS (P_g) 31 PSF

WIND LOADS

WIND SPEED 105 MPH
EXPOSURE C

SEISMIC LOADS

Ss 1.39 g
S1 0.52 g
SITE CLASS D (DEFAULT)

THE LOADS SHOWN ON THIS PAGE
ARE ONLY USED TO REVIEW PEMB
FRAME LOADS (IF SUPPLIED)

FOUNDATION CRITERIA

SOILS REPORT

COMPANY	TERRACON
DATE	12/27/2024
NUMBER	61245209

ALLOWABLE BEARING PRESSURE	1400	PSF
1/3 INCREASE FOR TEMPORARY LOADS:	1862	PSF
PASSIVE PRESSURE	315	PSF
ACTIVE PRESSURE	45	PSF
AT REST PRESSURE	60	PSF
COEFFICIENT OF FRICTION (μ)	0.45	



Hazelwood Engineering
Salt Lake City, UT

Project

Job Ref.

Section

Sheet no./rev.
1

Calc. by
S

Date
2/27/2025

Chk'd by

Date

App'd by

Date

FOOTING ANALYSIS

In accordance with ACI318-14

Tedds calculation version 3.3.08


Summary results

Overall design status PASS
Overall design utilisation 0.791

Description	Unit	Applied	Resisting	FoS	Result
Uplift verification	kips	35.9			Pass
Overturning stability, x	kip_ft	109.07	-170.46	1.56	Pass
Sliding stability, x	kips	8.2	16.1	1.969	Pass
Description	Unit	Applied	Resisting	Utilization	Result
Soil bearing	ksf	1.472	1.86	0.791	Pass
Description	Unit	Required	Provided	Utilization	Result
Moment, positive, x-direction	kip_ft	81.8	564.1	0.145	Pass
Moment, negative, x-direction	kip_ft	46.2	602.7	0.077	Pass
Moment, positive, y-direction	kip_ft	1.5	544.8	0.003	Pass
Shear, one-way, x-direction	kips	23.9	193.4	0.123	Pass
Shear, one-way, y-direction	kips	0.4	187.0	0.002	Pass
Min.area of reinf, bot., x-direction	in ²	5.335	5.720		Pass
Min.area of reinf, top, x-direction	in ²	5.335	5.720		Pass
Max.reinf.spacing, top, x-direction	in	18.0	9.1		Pass
Min.area of reinf, bot., y-direction	in ²	5.335	5.720		Pass
Max.reinf.spacing, bot, y-direction	in	18.0	9.1		Pass

Pad footing details

Length of footing $L_x = 9.5$ ft
Width of footing $L_y = 9.5$ ft
Footing area $A = L_x \times L_y = 90.25$ ft²
Depth of footing $h = 26$ in
Depth of soil over footing $h_{\text{soil}} = 6$ in
Density of concrete $\gamma_{\text{conc}} = 150.0$ lb/ft³



Column no.1 details

Length of column

 $l_{x1} = 12.00$ in

Width of column

 $l_{y1} = 12.00$ in

position in x-axis

 $x_1 = 57.00$ in

position in y-axis

 $y_1 = 57.00$ in

Soil properties

Gross allowable bearing pressure

 $Q_{allow_Gross} = 1.86$ ksf

Density of soil

 $\gamma_{soil} = 120.0$ lb/ft³

Angle of internal friction

 $\phi_b = 30.0$ deg

Design base friction angle

 $\delta_{bb} = 24.2$ deg

Coefficient of base friction

 $\tan(\delta_{bb}) = 0.450$

Footing loads

Self weight

 $F_{swt} = h \times \gamma_{conc} = 325$ psf

Soil weight

 $F_{soil} = h_{soil} \times \gamma_{soil} = 60$ psf

Column no.1 loads

Dead load in z

 $F_{Dz1} = 1.2$ kips

Dead load in x

 $F_{Dx1} = 8.2$ kips

Dead load moment in x

 $M_{Dx1} = 91.3$ kip_ft

Footing analysis for soil and stability

Load combinations per ASCE 7-16

1.0D (0.791)

Combination 1 results: 1.0D

Project				Job Ref.	
Section				Sheet no./rev. 3	
Calc. by S	Date 2/27/2025	Chk'd by	Date	App'd by	Date

Forces on footing

Force in x-axis

$$F_{dx} = \gamma_D \times F_{Dx1} = \mathbf{8.2 \text{ kips}}$$

Force in z-axis

$$F_{dz} = \gamma_D \times A \times (F_{swt} + F_{soil}) + \gamma_D \times (F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil}) = \mathbf{35.9 \text{ kips}}$$

Moments on footing

Moment in x-axis, about x is 0

$$M_{dx} = \gamma_D \times (A \times (F_{swt} + F_{soil}) \times L_x / 2) + \gamma_D \times (((F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil})) \times x_1 + M_{Dx1} + F_{Dx1} \times (h)) = \mathbf{279.5 \text{ kip_ft}}$$

Moment in y-axis, about y is 0

$$M_{dy} = \gamma_D \times (A \times (F_{swt} + F_{soil}) \times L_y / 2) + \gamma_D \times (((F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil})) \times y_1) = \mathbf{170.5 \text{ kip_ft}}$$

Uplift verification

Vertical force

$$F_{dz} = \mathbf{35.886 \text{ kips}}$$

PASS - Footing is not subject to uplift

Stability against overturning in x direction, moment about x is L_x

Overturning moment

$$M_{OTxL} = \gamma_D \times (M_{Dx1} + F_{Dx1} \times (h)) = \mathbf{109.07 \text{ kip_ft}}$$

Resisting moment

$$M_{RXL} = -1 \times (\gamma_D \times (A \times (F_{swt} + F_{soil}) \times L_x / 2)) + \gamma_D \times (((F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil})) \times (x_1 - L_x)) = \mathbf{-170.46 \text{ kip_ft}}$$

Factor of safety

$$\text{abs}(M_{RXL} / M_{OTxL}) = \mathbf{1.563}$$

PASS - Overturning moment safety factor exceeds the minimum of 1.50

Stability against sliding

Resistance due to base friction

$$F_{R\text{Friction}} = \max(F_{dz}, 0 \text{ kN}) \times \tan(\delta_{bb}) = \mathbf{16.149 \text{ kips}}$$

Stability against sliding in x direction

Total sliding resistance

$$F_{Rx} = F_{R\text{Friction}} = \mathbf{16.149 \text{ kips}}$$

Factor of safety

$$\text{abs}(F_{Rx} / F_{dx}) = \mathbf{1.97}$$

PASS - Sliding factor of safety exceeds the minimum of 1.50

Bearing resistance

Eccentricity of base reaction

Eccentricity of base reaction in x-axis

$$e_{dx} = M_{dx} / F_{dz} - L_x / 2 = \mathbf{36.471 \text{ in}}$$

Eccentricity of base reaction in y-axis

$$e_{dy} = M_{dy} / F_{dz} - L_y / 2 = \mathbf{0 \text{ in}}$$

Length of bearing in x-axis

$$L'_{xd} = \min(L_x, 3 \times (L_x / 2 - \text{abs}(e_{dx}))) = \mathbf{61.588 \text{ in}}$$

Pad base pressures

$$q_1 = \mathbf{0 \text{ ksf}}$$

$$q_2 = \mathbf{0 \text{ ksf}}$$

$$q_3 = \mathbf{1.472 \text{ ksf}}$$

$$q_4 = \mathbf{1.472 \text{ ksf}}$$

Minimum base pressure

$$q_{\min} = \min(q_1, q_2, q_3, q_4) = \mathbf{0 \text{ ksf}}$$

Maximum base pressure

$$q_{\max} = \max(q_1, q_2, q_3, q_4) = \mathbf{1.472 \text{ ksf}}$$

Allowable bearing capacity

Allowable bearing capacity

$$q_{\text{allow}} = q_{\text{allow_Gross}} = \mathbf{1.86 \text{ ksf}}$$

$$q_{\max} / q_{\text{allow}} = \mathbf{0.791}$$

PASS - Allowable bearing capacity exceeds design base pressure

Project				Job Ref.	
Section				Sheet no./rev. 4	
Calc. by S	Date 2/27/2025	Chk'd by	Date	App'd by	Date

FOOTING DESIGN

In accordance with ACI318-14

Tedds calculation version 3.3.08

Material details

Compressive strength of concrete	$f'_c = 2500$ psi
Yield strength of reinforcement	$f_y = 60000$ psi
Compression-controlled strain limit (21.2.2)	$\epsilon_{ty} = 0.00200$
Cover to top of footing	$c_{nom_t} = 1.5$ in
Cover to side of footing	$c_{nom_s} = 2$ in
Cover to bottom of footing	$c_{nom_b} = 3$ in
Concrete type	Normal weight
Concrete modification factor	$\lambda = 1.00$
Column type	Concrete

Analysis and design of concrete footing

Load combinations per ASCE 7-16

1.4D (0.145)

Combination 1 results: 1.4D

Forces on footing

Ultimate force in x-axis	$F_{ux} = \gamma_D \times F_{Dx1} = 11.5$ kips
Ultimate force in z-axis	$F_{uz} = \gamma_D \times A \times (F_{swt} + F_{soil}) + \gamma_D \times (F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil}) = 50.2$ kips

Moments on footing

Ultimate moment in x-axis, about x is 0	$M_{ux} = \gamma_D \times (A \times (F_{swt} + F_{soil}) \times L_x / 2) + \gamma_D \times (((F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil})) \times x_1 + M_{Dx1} + F_{Dx1} \times (h)) = 391.3$ kip_ft
Ultimate moment in y-axis, about y is 0	$M_{uy} = \gamma_D \times (A \times (F_{swt} + F_{soil}) \times L_y / 2) + \gamma_D \times (((F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil})) \times y_1) = 238.6$ kip_ft

Eccentricity of base reaction

Eccentricity of base reaction in x-axis	$e_{ux} = M_{ux} / F_{uz} - L_x / 2 = 36.471$ in
Eccentricity of base reaction in y-axis	$e_{uy} = M_{uy} / F_{uz} - L_y / 2 = 0$ in
Length of bearing in x-axis	$L'_{xu} = \min(L_x, 3 \times (L_x / 2 - \text{abs}(e_{ux}))) = 61.588$ in

Pad base pressures


	$q_{u1} = 0$ ksf
	$q_{u2} = 0$ ksf
	$q_{u3} = 2.061$ ksf
	$q_{u4} = 2.061$ ksf
Minimum ultimate base pressure	$q_{umin} = \min(q_{u1}, q_{u2}, q_{u3}, q_{u4}) = 0$ ksf
Maximum ultimate base pressure	$q_{umax} = \max(q_{u1}, q_{u2}, q_{u3}, q_{u4}) = 2.061$ ksf

Shear diagram, x axis (kips)



Project				Job Ref.	
Section				Sheet no./rev. 5	
Calc. by S	Date 2/27/2025	Chk'd by	Date	App'd by	Date

Moment diagram, x axis (kip_ft)



Moment design, x direction, positive moment

Ultimate bending moment $M_{u.x,max} = 81.765$ kip_ft
Tension reinforcement provided 13 No.6 bottom bars (9.1 in c/c)
Area of tension reinforcement provided $A_{sx,bot,prov} = 5.72$ in²
Minimum area of reinforcement (8.6.1.1) $A_{s,min} = 0.0018 \times L_y \times h = 5.335$ in²

PASS - Area of reinforcement provided exceeds minimum

Maximum spacing of reinforcement (8.7.2.2) $s_{max} = \min(2 \times h, 18 \text{ in}) = 18$ in

PASS - Maximum permissible reinforcement spacing exceeds actual spacing

Depth to tension reinforcement $d = h - c_{nom,b} - \phi_{x,bot} / 2 = 22.625$ in
Depth of compression block $a = A_{sx,bot,prov} \times f_y / (0.85 \times f'_c \times L_y) = 1.417$ in
Neutral axis factor $\beta_1 = 0.85$
Depth to neutral axis $c = a / \beta_1 = 1.667$ in
Strain in tensile reinforcement $\epsilon_t = 0.003 \times d / c - 0.003 = 0.03772$
Minimum tensile strain(8.3.3.1) $\epsilon_{min} = 0.004 = 0.00400$

PASS - Tensile strain exceeds minimum required

Nominal moment capacity $M_n = A_{sx,bot,prov} \times f_y \times (d - a / 2) = 626.816$ kip_ft
Flexural strength reduction factor $\phi_f = \min(\max(0.65 + 0.25 \times (\epsilon_t - \epsilon_{ty}) / (0.005 - \epsilon_{ty}), 0.65), 0.9) = 0.900$
Design moment capacity $\phi M_n = \phi_f \times M_n = 564.134$ kip_ft
 $M_{u.x,max} / \phi M_n = 0.145$

PASS - Design moment capacity exceeds ultimate moment load

Moment design, x direction, negative moment

Ultimate bending moment $M_{u.x,min} = -46.237$ kip_ft
Tension reinforcement provided 13 No.6 top bars (9.1 in c/c)
Area of tension reinforcement provided $A_{sx,top,prov} = 5.72$ in²
Minimum area of reinforcement (8.6.1.1) $A_{s,min} = 0.0018 \times L_y \times h = 5.335$ in²

PASS - Area of reinforcement provided exceeds minimum

Maximum spacing of reinforcement (8.7.2.2) $s_{max} = \min(2 \times h, 18 \text{ in}) = 18$ in

PASS - Maximum permissible reinforcement spacing exceeds actual spacing

Depth to tension reinforcement $d = h - c_{nom,t} - \phi_{x,top} / 2 = 24.125$ in
Depth of compression block $a = A_{sx,top,prov} \times f_y / (0.85 \times f'_c \times L_y) = 1.417$ in
Neutral axis factor $\beta_1 = 0.85$
Depth to neutral axis $c = a / \beta_1 = 1.667$ in
Strain in tensile reinforcement $\epsilon_t = 0.003 \times d / c - 0.003 = 0.04042$
Minimum tensile strain(8.3.3.1) $\epsilon_{min} = 0.004 = 0.00400$

Project				Job Ref.	
Section				Sheet no./rev. 6	
Calc. by S	Date 2/27/2025	Chk'd by	Date	App'd by	Date

PASS - Tensile strain exceeds minimum required

Nominal moment capacity

$$M_n = A_{s_{x,top,prov}} \times f_y \times (d - a / 2) = 669.716 \text{ kip_ft}$$

Flexural strength reduction factor

$$\phi_f = \min(\max(0.65 + 0.25 \times (\epsilon_t - \epsilon_{ty}) / (0.005 - \epsilon_{ty}), 0.65), 0.9) = 0.900$$

Design moment capacity

$$\phi M_n = \phi_f \times M_n = 602.744 \text{ kip_ft}$$

$$\text{abs}(M_{u,x,min}) / \phi M_n = 0.077$$

PASS - Design moment capacity exceeds ultimate moment load

One-way shear design, x direction

Ultimate shear force

$$V_{u,x} = 23.854 \text{ kips}$$

Depth to reinforcement

$$d_v = \min(h - C_{nom_b} - \phi_{x,bot} / 2, h - C_{nom_t} - \phi_{x,top} / 2) = 22.625 \text{ in}$$

Shear strength reduction factor

$$\phi_v = 0.75$$

Nominal shear capacity (Eq. 22.5.5.1)

$$V_n = 2 \times \lambda \times \sqrt{f'_c \times 1 \text{ psi}} \times L_y \times d_v = 257.925 \text{ kips}$$


Design shear capacity

$$\phi V_n = \phi_v \times V_n = 193.444 \text{ kips}$$


$$V_{u,x} / \phi V_n = 0.123$$

PASS - Design shear capacity exceeds ultimate shear load

Shear diagram, y axis (kips)



Moment diagram, y axis (kip_ft)



Moment design, y direction, positive moment

Ultimate bending moment

$$M_{u,y,max} = 1.517 \text{ kip_ft}$$

Tension reinforcement provided

$$13 \text{ No.6 bottom bars (9.1 in c/c)}$$

Area of tension reinforcement provided

$$A_{s_{y,bot,prov}} = 5.72 \text{ in}^2$$

Minimum area of reinforcement (8.6.1.1)

$$A_{s,min} = 0.0018 \times L_x \times h = 5.335 \text{ in}^2$$

PASS - Area of reinforcement provided exceeds minimum

Maximum spacing of reinforcement (8.7.2.2)

$$s_{max} = \min(2 \times h, 18 \text{ in}) = 18 \text{ in}$$

PASS - Maximum permissible reinforcement spacing exceeds actual spacing

Depth to tension reinforcement

$$d = h - C_{nom_b} - \phi_{x,bot} - \phi_{y,bot} / 2 = 21.875 \text{ in}$$

Depth of compression block

$$a = A_{s_{y,bot,prov}} \times f_y / (0.85 \times f'_c \times L_x) = 1.417 \text{ in}$$

Neutral axis factor

$$\beta_1 = 0.85$$

Depth to neutral axis

$$c = a / \beta_1 = 1.667 \text{ in}$$

Strain in tensile reinforcement

$$\epsilon_t = 0.003 \times d / c - 0.003 = 0.03637$$

Minimum tensile strain(8.3.3.1)

$$\epsilon_{min} = 0.004 = \mathbf{0.00400}$$

PASS - Tensile strain exceeds minimum required

Nominal moment capacity

$$M_n = A_{sy,bot,prov} \times f_y \times (d - a / 2) = \mathbf{605.366 \text{ kip_ft}}$$

Flexural strength reduction factor

$$\phi_f = \min(\max(0.65 + 0.25 \times (\epsilon_t - \epsilon_{ty}) / (0.005 - \epsilon_{ty}), 0.65), 0.9) = \mathbf{0.900}$$

Design moment capacity

$$\phi M_n = \phi_f \times M_n = \mathbf{544.829 \text{ kip_ft}}$$

$$M_{u,y,max} / \phi M_n = \mathbf{0.003}$$

PASS - Design moment capacity exceeds ultimate moment load

One-way shear design, y direction

Ultimate shear force

$$V_{u,y} = \mathbf{0.408 \text{ kips}}$$

Depth to reinforcement

$$d_v = \min(h - C_{nom_b} - \phi_{x,bot} - \phi_{y,bot} / 2, h - C_{nom_t} - \phi_{y,top} / 2) = \mathbf{21.875 \text{ in}}$$

Shear strength reduction factor

$$\phi_v = \mathbf{0.75}$$

Nominal shear capacity (Eq. 22.5.5.1)

$$V_n = 2 \times \lambda \times \sqrt{f'_c \times 1 \text{ psi}} \times L_x \times d_v = \mathbf{249.375 \text{ kips}}$$

Design shear capacity

$$\phi V_n = \phi_v \times V_n = \mathbf{187.031 \text{ kips}}$$

$$V_{u,y} / \phi V_n = \mathbf{0.002}$$

PASS - Design shear capacity exceeds ultimate shear load

Two-way shear design at column 1

Depth to reinforcement

$$d_{v2} = \mathbf{22.25 \text{ in}}$$

Shear perimeter length (22.6.4)

$$l_{xp} = \mathbf{74.125 \text{ in}}$$

Shear perimeter width (22.6.4)

$$l_{yp} = \mathbf{74.125 \text{ in}}$$

Shear perimeter (22.6.4)

$$b_o = l_{x,perim} + l_{y,perim} = \mathbf{148.250 \text{ in}}$$

Shear area

$$A_p = l_{x,perim} \times l_{y,perim} = \mathbf{5494.516 \text{ in}^2}$$

Surcharge loaded area

$$A_{sur} = A_p - l_{x1} \times l_{y1} = \mathbf{5350.516 \text{ in}^2}$$

Ultimate bearing pressure at center of shear area

$$q_{up,avg} = \mathbf{2.575 \text{ ksf}}$$

Ultimate shear load

$$F_{up} = \gamma_D \times (F_{Dz1} - l_{x1} \times l_{y1} \times h_{soil} \times \gamma_{soil}) + \gamma_D \times A_p \times F_{swt} + \gamma_D \times A_{sur} \times F_{soil} - q_{up,avg} \times A_p = \mathbf{-76.156 \text{ kips}}$$

Ultimate shear stress from vertical load

$$v_{ug} = \max(F_{up} / (b_o \times d_{v2}), 0 \text{ psi}) = \mathbf{0.000 \text{ psi}}$$

Column geometry factor (Table 22.6.5.2)

$$\beta = l_{y1} / l_{x1} = \mathbf{1.00}$$

Column location factor (22.6.5.3)

$$\alpha_s = \mathbf{20}$$

Concrete shear strength (22.6.5.2)

$$v_{cpa} = (2 + 4 / \beta) \times \lambda \times \sqrt{f'_c \times 1 \text{ psi}} = \mathbf{300.000 \text{ psi}}$$

$$v_{cpb} = (\alpha_s \times d_{v2} / b_o + 2) \times \lambda \times \sqrt{f'_c \times 1 \text{ psi}} = \mathbf{250.084 \text{ psi}}$$

$$v_{cpc} = 4 \times \lambda \times \sqrt{f'_c \times 1 \text{ psi}} = \mathbf{200.000 \text{ psi}}$$

$$v_{cp} = \min(v_{cpa}, v_{cpb}, v_{cpc}) = \mathbf{200.000 \text{ psi}}$$

Shear strength reduction factor

$$\phi_v = \mathbf{0.75}$$

Nominal shear stress capacity (Eq. 22.6.1.2)


$$v_n = v_{cp} = \mathbf{200.000 \text{ psi}}$$

Design shear stress capacity (8.5.1.1(d))

$$\phi v_n = \phi_v \times v_n = \mathbf{150.000 \text{ psi}}$$

$$v_{ug} / \phi v_n = \mathbf{0.000}$$

PASS - Design shear stress capacity exceeds ultimate shear stress load



13 No.6 bottom bars (9.1 in c/c)
13 No.6 top bars (9.1 in c/c)

13 No.6 bottom bars (9.1 in c/c)
13 No.6 top bars (9.1 in c/c)